

MD2000 TITAN CL™

≈WIND≈ SERIES

Automatic Lubricator

The MD2000 TITAN CLTM CARTRIDGE LUBER.....

a powerful, motor-driven automatic lubricator which is refillable by simply replacing a standard grease cartridge.

Its microprocessor controlled, energy efficient motor delivers grease to a fixed displacement pump which produces pressures up to 900psi. This strength allows the **TITAN CLTM** to drive lubricant to several bearings consecutively through long feed lines using a progressive distribution block.



Features

- Most powerful lubricator on the market; produces up to 900psi which enables it to service single-point applications up to 30' away (9m.) and multi-point applications up to 20' (6m.) away.
- Available with long-life replaceable battery packs or optional external power sources. (AC and DC)
- · Single or Multi-point configuration.
- Refillable using a standard grease cartridge (no other tools needed).
- Able to service up to 12 lube points with optional progressive distribution block.

- Unit is mounted on an easy to install base plate.
- Optional remote control available to connect to customer supplied equipment or machinery. (eg: PLC, contactors, relays)
- Suitable for both land-based or off-shore Nacelles.
- Multiple settings from 15 days to 2 years.
- Built on proven technology used worldwide since 1982.
 Market Leader
- Designed for the toughest operating environments.

Temperature Range:

5°F to + 132°F (-15°C to + 55°C) (NOTE: Low Temp lubricants must be used at low temperatures)

Size:

Model WTCL 24-1/2" H X 6" W X 8" D (62cm H x 15cm W x 20cm D)



